



FEATURES :

- * Multi Speed Gear Box which is compatible with both 540 & 1000 RPM.
- * Hardened Gears for more longer life.
- * Tilling depth can be controlled with the adjustable skid shoe.
- * Heavy Trailing Board with Spring Shock Absorber.
- * Special Boron Steel material used for long life of blades.
- * Helical arrangement of Blades which makes it more effective and efficient
- * High tensile fasteners



Color Options



AVTAR ROTARY TILLER is one of the most suitable machine to till soil for seedbed or planting preparation, for removal of sugarcane stubble, cotton, banana, grass, vegetables & etc, it retains growth of crops to give you the best yield and profit. It can be used in dry and wet paddy condition for puddling and to till soil finely and improve the organic structure of the soil. The offset capabilities allow the tiller to work closer to the objects such as fence lines or trees. Operator can control the tilling depth with the adjustable skid shoe. Its unique design allows it to operate with minimum vibration in the field as well as less operating load on the tractor, So automatically decreasing the consumption of fuel.

SPECIFICATIONS

Description	AA-5 (5feet)	AA-6 (6feet)	AA-7 (7feet)	AA-8 (8feet)
Tractor power	35-45 HP	45-55 HP	55-65 HP	65 & Above
Over all width	175 cm	200 cm	225 cm	250 cm
Tillage width	150 cm	175 cm	200 cm	225 cm
Gear Box	Multi/Single Speed	Multi/Single Speed	Multi/Single Speed	Multi/Single Speed
P T O Speed	540/1000 rpm	540/1000 rpm	540/1000 rpm	540/1000 rpm
Rotor Speed	162-230 rpm	162-230 rpm	162-230 rpm	162-230 rpm
No. Blade	36	42	48	54
Approx. weight	430 kg	465 kg	510 kg	550 kg



PTO SHAFT



Harrow Disc



Gear Box



Helical Blades

AVTAR EXPORTS (INDIA)

Web : www.avtarexports.com

E-mail : info@avtarexports.com

Tel. : +91-99145-00732, +91-97810-98731